






SECURITY FOILING
DOCUMENT SECURITY SOLUTION PROVIDER

MicroPOISE™ Mk2 Sentry
Auto Card-Feeder PRO




ISO standard plastic cards
to **3500** impressions per hour
Security Access software
H : 37 W : 82 D : 41 (cm)

MicroPOISE™ stamps



DUOGRAM HD - HOLOGRAM - DATAFOIL HD

The simple solution for applying security features to



Credit and
other banking cards



National ID



Government ID projects



Driving licence



Student cards



Airport and
maritime security



Transport passes



Employee ID



Signature strips



Gift cards



This company supports the Metropolitan Police initiative to prevent the sales of equipment for illegal purposes. Information may be shared with Law Enforcement Agencies.



Unit 16, Boss Hall Road, Ipswich, Suffolk, IP1 5BN, England



securityfoiling.co.uk



info@securityfoiling.co.uk



+44 (0) 1473 708647



Automatic Card Feeding

Production speed

- Up to 3500 cards per hour depending on features being applied

Card type

- ISO standard plastic cards or similar

Feeding and stamping format

- Cards can be processed landscape or portrait to stamp features in any position on the card within 3mm from the card edge

Card Feeder

- 150 card stack feeds from the bottom and can be topped up for continuous production

Card stamping position

- Left to right by a 16 way programmable memory system allowing instant control of stamping position. Top to bottom by manual adjustment of card feeder

Security feature stamping area

- Within the max 65 x 30mm stamping area

MicroPOISE™ MK2 Sentry machine

Strong Impression system with adjustable die head to allow a very accurate level impression control

Foil Handling

- Maximum foil width 67 mm
- Maximum foil roll 100 mm diameter
- Maximum foil waste collection 100 mm diameter
- Foil core size from 25.4 up to 75 mm
- Hologram positional tolerance +/- 0.25 mm*
- Hologram registration mark 5 x 5 mm
- Bi-directional centered on image recommended

Impression System

- Stamping head Size 39 x 65mm
- Impression pressure up to 1000 kg
- Impression time from 0 to 10 seconds

Heating System

- Temperature 50 -150 degrees centigrade
- Heat-up cycle time 3 minutes

Power Supply

- Machine power supply 1 phase 220 - 240v
50Hz

General

- Combined desktop dimensions (cm)
Height - 37 Width - 33 Depth - 41
- Total gross weight 55kg

* subject to foil manufacturing tolerances

Other products in the MicroPOISE™ range

Paper sheet

Auto-Sheet Feeder
Auto-Sheet Feeder PRO
Auto-Sheet Feeder Vacuum

Continuous sheet

Auto-Sprocket Feeder

Plastic card

Auto-Card Feeder
Auto-Large Card Feeder

Roll to Roll

Auto-Roll Label Feeder PRO

Point of issue

Hand Fed
Document Template
Single-Card Feeder
Manual-Card Feeder



This company supports the Metropolitan Police initiative to prevent the sales of equipment for illegal purposes. Information may be shared with Law Enforcement Agencies.

The Metropolitan Police Service does not endorse any products, services or organisation's represented on this site.



Unit 16, Boss Hall Road, Ipswich, Suffolk, IP1 5BN, England



securityfoiling.co.uk



info@securityfoiling.co.uk



+44 (0) 1473 708647